

BOE**PROPRIETARY NOTE**

THIS SPECIFICATION IS THE PROPERTY OF BOE FZ AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF BOE FZ AND MUST BE RETURNED TO BOE FZ UPON ITS REQUEST

TITLE : MV230FHM-N40 Product Specification**Ver.0**

FUZHOU BOE OPTOELECTRONICS TECHNOLOGY CO. LTD

SPEC. NUMBER S864-8D003	PRODUCT GROUP TFT-LCD	Ver.0	ISSUE DATE 2018.4.9	PAGE 1 OF 29
----------------------------	--------------------------	-------	------------------------	-----------------

R2015-8006-O

A4(210 X 297)



BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	Ver.0	2018.4.9

REVISION HISTORY

() Preliminary specification

(●) Final specification

Revision No.	Page	Description of changes	Date	Prepared
Ver. 0		Initial Release	2018.4.9	Zhao Hongyu

SPEC. NUMBER S864-8D003	SPEC. TITLE B10 MV230FHM-N40 Product Specification Ver.0	PAGE 2 OF 29
----------------------------	---	-----------------

R2015-8006-O

A4(210 X 297)

BOE**PRODUCT GROUP**

REV

ISSUE DATE

TFT- LCD PRODUCT

Ver.0

2018.4.9

Contents

No.	Item	Page
1.0	General Description	4
2.0	Absolute Maximum Ratings	6
3.0	Electrical Specifications	7
4.0	Optical Specifications	8
5.0	Interface Connection	10
6.0	Signal Timing Specifications	13
7.0	Signal Timing Waveforms of Interface Signal	15
8.0	Input Signals, Display Colors & Gray Scale of Colors	17
9.0	Power Sequence	18
10.0	Mechanical Characteristics	19
11.0	Reliability Test	20
12.0	Handling& Cautions	21
13.0	Product Serial Number	22
14.0	Packing	23
15.0	Appendix	25

SPEC. NUMBER

S864-8D003

SPEC. TITLE

B10 MV230FHM-N40 Product Specification Ver.0

PAGE

3 OF 29

R2015-8006-O


A4(210 X 297)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	Ver.0	2018.4.9

1.0 GENERAL DESCRIPTION

1.1 Introduction

MV230FHM-N40 is a color active matrix TFT LCD module using amorphous silicon TFT's (Thin Film Transistors) as an active switching devices. This module has a 23.0 inch diagonally measured active area with FHD resolutions (1920 horizontal by 1080 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical stripe and this module can display 16.7M colors. The TFT-LCD panel used for this module is adapted for a low reflection and higher color type.



1.2 Features

- LVDS Interface with 2 pixel / clock
- 6-bit (Hi-FRC) color depth, display 16. 7M colors
- wide viewing angle
- DE (Data Enable) only
- RoHS/Halogen Free
- Gamma Correction
- Reverse type

SPEC. NUMBER S864-8D003	SPEC. TITLE B10 MV230FHM-N40 Product Specification Ver.0	PAGE 4 OF 29
----------------------------	---	-----------------

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	Ver.0	2018.4.9

1.3 Application

- Desktop Type of PC & Workstation Use
- Slim-Size Display for Stand-alone Monitor
- Display Terminals for Control System
- Monitors for Process Controller

1.4 General Specification

The followings are general specifications at the model MV230FHM-N40.

<Table 1. General Specifications>

Parameter	Specification	Unit	Remarks
Active area	509.184(H) × 286.416(V)	mm	
Number of pixels	1920(H) × 1080(V)	pixels	
Pixel pitch	0.2652 (H) × 0.2652(V)	mm	
Pixel arrangement	RGB Vertical stripe		
Display colors	16.7M	colors	
Display mode	Normally Black		
Dimensional outline	517.2(H) x 302.8(V) x 12.3(D) typ.	mm	Detail refer to drawing
Weight	2100g (Typ.)	g	
Bezel width (L/R/U/D)	4/4/4/12.4	mm	
Surface Treatment	Haze 25%, 3H		
Back-light	Horizontal arranged, 1-LED Lighting Bar type		

SPEC. NUMBER S864-8D003	SPEC. TITLE B10 MV230FHM-N40 Product Specification Ver.0	PAGE 5 OF 29
----------------------------	---	-----------------

R2015-8006-O

A4(210 X 297)

BOE**PRODUCT GROUP**

REV

ISSUE DATE

TFT- LCD PRODUCT

Ver.0

2018.4.9

2.0 ABSOLUTE MAXIMUM RATINGS

The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit. The operational and non-operational maximum voltage and current values are listed in Table 2.

< Table 2. Absolute Maximum Ratings >

[VSS=GND=0V]


Parameter	Symbol	Min.	Max.	Unit	Remarks
Power Supply Voltage	V_{DD}	-0.3	6.0	V	Ta = 25 °C
Logic Supply Voltage	V_{IN}	VSS-0.3	$V_{DD}+0.3$	V	
Operating Temperature	T_{OP}	0	+50	°C	1)
Storage Temperature	T_{ST}	-20	+60	°C	1)
LCM Surface Temperature (Operation)	Tsurface	0	+65	°C	2)

Note : 1) Temperature and relative humidity range are shown in the figure below.

Wet bulb temperature should be 39 °C max. and no condensation of water.

2) Panel Surface Temperature should be Min. 0°C and Max. +65°C under the

VDD = 5.0V, Frame rate = 60Hz, 25°C ambient Temp. no humidity control and LED string current is typical value.



SPEC. NUMBER

S864-8D003

SPEC. TITLE

B10 MV230FHM-N40 Product Specification Ver.0

PAGE

6 OF 29

R2015-8006-O

A4(210 X 297)

BOE**PRODUCT GROUP**

REV

ISSUE DATE

TFT- LCD PRODUCT

Ver.0

2018.4.9

3.0 ELECTRICAL SPECIFICATIONS**3.1 Electrical Specifications**

< Table 3. Electrical specifications >

[Ta =25 ± 2 °C]

Parameter.		Min.	Typ.	Max.	Unit	Remarks
Power Supply Voltage	V _{DD}	4.5	5.0	5.5	V	Note1
Power Supply Current	I _{DD}	-	700	1000	mA	
In-Rush Current	I _{RUSH}	-	2.0	3.0	A	Note 2
Permissible Input Ripple Voltage	V _{RF}	-	-	300	mV	Note1,3
High Level Differential Input Threshold Voltage	V _{IH}	-	-	+100	mV	
Low Level Differential Input Threshold Voltage	V _{IL}	-100	-	-	mV	
Differential input voltage	V _{ID}	200	-	600	mV	
Differential input common mode voltage	V _{cm}	1.0	1.2	1.5		V _{IH} =100mV, V _{IL} =-100mV
Power Consumption	P _D	-	3.5	5.0	W	
	P _{BL}	-	10.08	10.75	W	Note 4
	P _{total}	-	13.58	15.75	W	


Notes : 1. The supply voltage is measured and specified at the interface connector of LCM.

The current draw and power consumption specified is for VDD=5.0V, Frame rate=60Hz

Clock frequency = 74.3 MHz. Test Pattern of power supply current



a) Typ : Color Test



b) Max : Vertical SubLine 255

2. Duration of rush current is about 2 ms and rising time of VDD is 520 μs ± 20 %

3. Ripple Voltage should be covered by Input voltage Spec.

4. Calculated value for reference (Input pins*VPIN × IPIN) excluding inverter loss.

SPEC. NUMBER

S864-8D003

SPEC. TITLE

B10 MV230FHM-N40 Product Specification Ver.0

PAGE

7 OF 29

R2015-8006-O

A4(210 X 297)

BOE**PRODUCT GROUP**

REV

ISSUE DATE

TFT- LCD PRODUCT

Ver.0

2018.4.9

3.2 Backlight Unit

< Table 4. LED Backlight Unit >

Parameter		Min.	Typ.	Max.	Unit	Remarks
LED Light Bar Input Voltage Per Input Pin	VPIN	-	63.0	67.2	V	Duty 100%
LED Light Bar Input Current Per Input Pin	IPIN	-	40	50	mA	Note1,2
LED Power Consumption	P _{BL}	-	10.08	10.75	W	Note 3
LED Life-Time	-	30,000	-		Hrs	Note 4

LED bar consists of 84 LED packages,4strings(parallel)*21packages(serial)

Note1: There are one light bar ,and the specified current is input LED chip 100% duty current

Note2: The sense current of each input pin is 50mA

Note3: $P_{BL}=4\text{Input pins} \times V_{PIN} \times I_{PIN}$

Note4: The lifetime is determined as the time at which luminance of LED become 50% of the initial brightness or not normal lighting at $I_{PIN}=40\text{mA}$ on condition of continuous operating at $25 \pm 2 \text{ } ^\circ\text{C}$

SPEC. NUMBER

S864-8D003

SPEC. TITLE

B10 MV230FHM-N40 Product Specification Ver.0

PAGE

8 OF 29

R2015-8006-O

A4(210 X 297)

BOE**PRODUCT GROUP**

REV

ISSUE DATE

TFT- LCD PRODUCT

Ver.0

2018.4.9

4.0 OPTICAL SPECIFICATION**4.1 Overview**

The test of Optical specifications shall be measured in a dark room (ambient luminance ≤ 1 lux and temperature = $25 \pm 2^\circ\text{C}$) with the equipment of Luminance meter system (Goniometer system and TOPCONE PR730) and test unit shall be located at an approximate distance 50cm from the LCD surface at a viewing angle of θ and Φ equal to 0° . We refer to $\theta_{0=0}$ ($=\theta_3$) as the 3 o'clock direction (the "right"), $\theta_{0=90}$ ($=\theta_{12}$) as the 12 o'clock direction ("upward"), $\theta_{0=180}$ ($=\theta_9$) as the 9 o'clock direction ("left") and $\theta_{0=270}$ ($=\theta_6$) as the 6 o'clock direction ("bottom"). While scanning θ and/or Φ , the center of the measuring spot on the Display surface shall stay fixed. The measurement shall be executed after 30 minutes warm-up period. VDD shall be 5.0V +/-10% at 25°C . Optimum viewing angle direction is 6 'clock.

4.2 Optical Specifications[VDD = 5.0V, Frame rate = 60Hz, Clock = 74.25MHz, $I_{BL} = 200\text{mA}$, $T_a = 25 \pm 2^\circ\text{C}$]

Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Viewing Angle range	Horizontal	Θ_3	CR > 10	85	89	-	Deg.	Note 1
		Θ_9		85	89	-	Deg.	
	Vertical	Θ_{12}		85	89	-	Deg.	
		Θ_6		85	89	-	Deg.	
Luminance Contrast ratio		CR		700	1000			Note 2
Luminance of White		Y_w		200	250		cd/m ²	Note 3
White luminance uniformity		ΔY		75	-		%	Note 4
Reproduction of color	White	W_x	$\Theta = 0^\circ$ (Center) Normal Viewing Angle	0.283	0.313	0.343	-	Note 5
		W_y		0.299	0.329	0.359	-	
	Red	R_x		0.632	0.662	0.692	-	
		R_y		0.302	0.332	0.362	-	
	Green	G_x		0.288	0.318	0.348	-	
		G_y		0.607	0.637	0.667	-	
	Blue	B_x		0.122	0.152	0.182	-	
		B_y		0.025	0.055	0.085	-	
Response Time	GTG	T_g		14	20	ms	Note 6	

SPEC. NUMBER

S864-8D003

SPEC. TITLE

B10 MV230FHM-N40 Product Specification Ver.0

PAGE

9 OF 29

R2015-8006-O

A4(210 X 297)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	Ver.0	2018.4.9

Note :

- Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface.
- Contrast measurements shall be made at viewing angle of $\theta = 0^\circ$ and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state. (See FIGURE 1 shown in Appendix) Luminance Contrast Ratio (CR) is defined mathematically.

$$CR = \frac{\text{Luminance when displaying a white raster}}{\text{Luminance when displaying a black raster}}$$

- Center Luminance of white is defined as the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display.
- The White luminance uniformity on LCD surface is then expressed as :

$$\Delta Y = (\text{Minimum Luminance of 9points} / \text{Maximum Luminance of 9points}) * 100$$
 (See FIGURE 2 shown in Appendix).
- The color chromaticity coordinates specified in Table 4. shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel.
- Response time Tg is the average time required for display transition by switching the input signal as below table and is based on Frame rate fV =60Hz to optimize.
Each time in below table is defined as Figure 3and shall be measured by switching the input signal for "any level of gray(bright)"and "any level of gray(dark)".

SPEC. NUMBER S864-8D003	SPEC. TITLE B10 MV230FHM-N40 Product Specification Ver.0	PAGE 10 OF 29
----------------------------	---	------------------

R2015-8006-O

A4(210 X 297)

BOE**PRODUCT GROUP**

REV

ISSUE DATE

TFT- LCD PRODUCT

Ver.0


2018.4.9

5.0 INTERFACE CONNECTION.**5.1 Electrical Interface Connection****5.1.1 LED Light Bar**

-LED connector: 3712K-Q06M-00R(ENTERY) or EQUIVALENT

< Table 1. LED Light Bar >

Pin No	Symbol	Description
1	IRLED1	LED current sense for string1
2	IRLED2	LED current sense for string2
3	VLED	LED power supply
4	VLED	LED power supply
5	IRLED3	LED current sense for string3
6	IRLED4	LED current sense for string4

SPEC. NUMBER
S864-8D003SPEC. TITLE
B10 MV230FHM-N40 Product Specification Ver.0PAGE
11 OF 29

R2015-8006-O

A4(210 X 297)

BOE**PRODUCT GROUP**

REV

ISSUE DATE

TFT- LCD PRODUCT

Ver.0

2018.4.9

5.0 INTERFACE CONNECTION.**5.1 Electrical Interface Connection**

- CN101 Module Side Connector : UJU IS100-L300-C23or Equivalent
User Side Connector : JAE FI-X30H or Equivalent

Pin No	Symbol	Function	Remark
1	RX00-	Negative Transmission data of Pixel 0 (ODD)	
2	RX00+	Positive Transmission data of Pixel 0 (ODD)	
3	RX01-	Negative Transmission data of Pixel 1 (ODD)	
4	RX01+	Positive Transmission data of Pixel 1 (ODD)	
5	RX02-	Negative Transmission data of Pixel 2 (ODD)	
6	RX02+	Positive Transmission data of Pixel 2 (ODD)	
7	NC	NC/GND	
8	RXOC-	Negative Transmission Clock (ODD)	
9	RXOC+	Positive Transmission Clock (ODD)	
10	RX03-	Negative Transmission data of Pixel 3 (ODD)	
11	RX03+	Positive Transmission data of Pixel 3 (ODD)	
12	RXE0-	Negative Transmission data of Pixel 0 (EVEN)	
13	RXE0+	Positive Transmission data of Pixel 0 (EVEN)	
14	GND	Power Ground	
15	RXE1-	Negative Transmission data of Pixel 1 (EVEN)	
16	RXE1+	Positive Transmission data of Pixel 1 (EVEN)	
17	GND	Power Ground	
18	RXE2-	Negative Transmission data of Pixel 2 (EVEN)	
19	RXE2+	Positive Transmission data of Pixel 2 (EVEN)	
20	RXEC-	Negative Transmission Clock (EVEN)	
21	RXEC+	Positive Transmission Clock (EVEN)	
22	RXE3-	Negative Transmission data of Pixel 3 (EVEN)	
23	RXE3+	Positive Transmission data of Pixel 3 (EVEN)	
24	GND	Power Ground	Note 1
25	NC	No Connection	
26	NC	No Connection	
27	NC	No Connection	
28	VDD	Power Supply: +5V	
29	VDD		
30	VDD		

Note 1: This pin should be connected with GND.

SPEC. NUMBER

S864-8D003

SPEC. TITLE

B10 MV230FHM-N40 Product Specification Ver.0

PAGE

12 OF 29

R2015-8006-O

A4(210 X 297)

BOE**PRODUCT GROUP**

REV

ISSUE DATE

TFT- LCD PRODUCT

Ver.0

2018.4.9

5.2 LVDS Interface (Tx; THC63LVDF83A or Equivalent)**5.2.1 LVDS Interface**

	Input Signal	Transmitter		Interface		HT236F01-100 (CN11)	Remark
		Pin No.	Pin No.	System (Tx)	TFT-LCD (Rx)	Pin No.	
L V D S	OR0	51	48 47	OUT0- OUT0+	RX00- RX00+	1 2	
	OR1	52					
	OR2	54					
	OR3	55					
	OR4	56					
	OR5	3					
	OG0	4	46 45	OUT1- OUT1+	RX01- RX01+	3 4	
	OG1	6					
	OG2	7					
	OG3	11					
	OG4	12					
	OG5	14					
	OB0	15	42 41	OUT2- OUT2+	RX02- RX02+	5 6	
	OB1	19					
	OB2	20					
	OB3	22					
	OB4	23					
	OB5	24					
	Hsync	27	40 39	CLK OUT- CLK OUT+	RX0 CLK- RX0 CLK+	8 9	
	Vsync	28					
	DE	30	38 37	OUT3- OUT3+	RX03- RX03+	10 11	
	MCLK	31					
	OR6	50					
	OR7	2					
OG6	8						
OG7	10						
OB6	16						
OB7	18						
RSVD	25						

Note: The order of even data is same with odd data.

SPEC. NUMBER

S864-8D003

SPEC. TITLE

B10 MV230FHM-N40 Product Specification Ver.0

PAGE

13 OF 29

R2015-8006-O

A4(210 X 297)

BOE**PRODUCT GROUP**

REV

ISSUE DATE

TFT- LCD PRODUCT

Ver.0

2018.4.9

6.0 SIGNAL TIMING SPECIFICATION

6.1 The MV230FHM-N40 is operated by the DE only.

Item	Symbols		Min	Typ	Max	Unit	Note
DCLK	Period	tCLK	10.47	13.47	16.84	ns	
	Frequency	-	59.4	74.25	95.5	MHz	
Hsync	Period	tHP	1050	1100	1120	tCLK	
	Horizontal Valid	tHV	960	960	960	tCLK	
	Horizontal Blank	tHB	90	140	160		
	Frequency	fH	56	67.5	84.5	KHz	
Vsync	Period	tVP	1110	1125	1300	tHP	2)
	Vertical Valid	tVV	1080	1080	1080	tHP	
	Vertical Blank	tVB	30	45	171	tHP	
	Frequency	fV	50	60	77	Hz	3)
LVDS Receiver clock	Input spread spectrum ratio	SSr	-3	-	+3	%	
	Spread spectrum modulation frequency	F _{SSM}	-	-	200	KHz	

Note: 1). The DCLK range at last line of V-blanking should be set in 0~987.

2). The Hsync Period maximum can reach 1300tHP when the mode is applied @1080i 50Hz.

3). The Vsync Frequency maximum can reach 77Hz when the resolution is applied as the mode listed in the following table.

Mode	Panel Timing (Htotal*Vtotal)
1024*768	2100*1125
1152*870	2100*1136
1152*900	2100*1132
1280*1024	2100*1125

SPEC. NUMBER

S864-8D003

SPEC. TITLE

B10 MV230FHM-N40 Product Specification Ver.0

PAGE

14 OF 29

R2015-8006-O

A4(210 X 297)

BOE

PRODUCT GROUP

REV

ISSUE DATE

TFT- LCD PRODUCT

Ver.0


2018.4.9

6.2 LVDS Rx Interface Timing Parameter

The specification of the LVDS Rx interface timing parameter is shown in Table 4.

<Table 4. LVDS Rx Interface Timing Specification>

Item	Symbol	Min	Typ	Max	Unit	Remark
CLKIN Period	tRCIP	10.47	13.47	16.84	nsec	
Input Data 0	tRIP1	-0.4	0.0	+0.4	nsec	
Input Data 1	tRIP0	tRCIP/7-0.4	tRCIP/7	tRCIP/7+0.4	nsec	
Input Data 2	tRIP6	2 × tRCIP/7-0.4	2 × tRCIP/7	2 × tRCIP/7+0.4	nsec	
Input Data 3	tRIP5	3 × tRCIP/7-0.4	3 × tRCIP/7	3 × tRCIP/7+0.4	nsec	
Input Data 4	tRIP4	4 × tRCIP/7-0.4	4 × tRCIP/7	4 × tRCIP/7+0.4	nsec	
Input Data 5	tRIP3	5 × tRCIP/7-0.4	5 × tRCIP/7	5 × tRCIP/7+0.4	nsec	
Input Data 6	tRIP2	6 × tRCIP/7-0.4	6 × tRCIP/7	6 × tRCIP/7+0.4	nsec	



$$* V_{diff} = (RXz+) - (RXz-), \dots, (RXCLK+) - (RXCLK-)$$

SPEC. NUMBER
S864-8D003

SPEC. TITLE
B10 MV230FHM-N40 Product Specification Ver.0

PAGE
15 OF 29

R2015-8006-O

A4(210 X 297)

BOE

PRODUCT GROUP


REV

ISSUE DATE

TFT- LCD PRODUCT

Ver.0

2018.4.9

6.3 LVDS DC Specification

$$|V_{ID}| = |(LVDS+) - (LVDS-)|$$

$$V_{CM} = \{(LVDS+) + (LVDS-)\} / 2$$

Differential input voltage	$ V_{ID} $	200	-	600	mV
Differential input common mode voltage	V_{CM}	1.0	1.2	1.5	V

SPEC. NUMBER

S864-8D003

SPEC. TITLE

B10 MV230FHM-N40 Product Specification Ver.0

PAGE

16 OF 29

R2015-8006-O


A4(210 X 297)



BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	Ver.0	2018.4.9


7.0 SIGNAL TIMING WAVEFORMS OF INTERFACE SIGNAL

7.1 Sync Timing Waveforms



- 1) Need over 3 H-sync during V-Sync Low
- 2) Fix H-Sync width from V-Sync falling edge to first rising edge

7.2 Vertical Timing Waveforms





SPEC. NUMBER S864-8D003	SPEC. TITLE B10 MV230FHM-N40 Product Specification Ver.0	PAGE 17 OF 29
----------------------------	---	------------------



BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	Ver.0	2018.4.9

7.3 Horizontal Timing Waveforms



SPEC. NUMBER S864-8D003	SPEC. TITLE B10 MV230FHM-N40 Product Specification Ver.0	PAGE 18 OF 29
----------------------------	---	------------------



PRODUCT GROUP

REV

ISSUE DATE

TFT- LCD PRODUCT

Ver.0

2018.4.9

8.0 INPUT SIGNALS, BASIC DISPLAY COLORS & GRAY SCALE OF COLORS

Color & Gray Scale		RED DATA								GREEN DATA								BLUE DATA							
		R7	R6	R5	R4	R3	R2	R1	R0	G7	G6	G5	G4	G3	G2	G1	G0	B7	B6	B5	B4	B3	B2	B1	B0
Basic Colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Green	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	Cyan	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
	Red	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Magenta	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Gray Scale of RED	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	△	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	Darker	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	△	↑								↑															
	▽	↓								↓															
	Brighter	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	▽	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	Red	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
Gray Scale of GREEN	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	△	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0		
	△	↑								↑															
	▽	↓								↓															
	Brighter	0	0	0	0	0	0	0	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0		
	▽	0	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0		
	Green	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0		
Gray Scale of BLUE	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	△	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	
	△	↑								↑															
	▽	↓								↓															
	Brighter	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	1	
	▽	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0	
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	
Gray Scale of WHITE	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	△	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	
	Darker	0	0	0	0	0	0	1	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1		
	△	↑								↑															
	▽	↓								↓															
	Brighter	1	1	1	1	1	1	0	1	1	1	1	1	1	0	1	1	1	1	1	1	0	1		
	▽	1	1	1	1	1	1	0	1	1	1	1	1	1	0	1	1	1	1	1	1	1	0		
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1		

SPEC. NUMBER
S864-8D003

SPEC. TITLE
B10 MV230FHM-N40 Product Specification Ver.0

PAGE
19 OF 29

R2015-8006-O

A4(210 X 297)

BOE**PRODUCT GROUP**

REV

ISSUE DATE


TFT- LCD PRODUCT

Ver.0

2018.4.9

9.0 POWER SEQUENCE

To prevent a latch-up or DC operation of the LCD module, the power on/off sequence shall be as shown in below.



- $0.5 \text{ ms} \leq T1 \leq 10 \text{ ms}$
- $0 \leq T2 \leq 50 \text{ ms}$
- $0 < T3 \leq 50 \text{ ms}$
- $1 \text{ sec} \leq T4$
- $200 \text{ ms} \leq T5$
- $200 \text{ ms} \leq T6$

Notes:

1. When the power supply VDD is 0V, keep the level of input signals on the low or keep high impedance.
2. Do not keep the interface signal high impedance when power is on.
3. Back Light must be turn on after power for logic and interface signal are valid.
4. T7 decreases smoothly, there is none re-bouncing voltage.
5. The above power sequence should be satisfied at these case
 - DC power On/Off
 - Mode Change (Resolution, frequency, timing, sleep mode, color depth change etc.)
 If not to follow power sequence, there is a risk of abnormal display.
6. If T3=0ms, there is a risk of flicker when power On/Off.
7. If T6=0ms, there is a risk of abnormal display when power off.

SPEC. NUMBER

S864-8D003

SPEC. TITLE

B10 MV230FHM-N40 Product Specification Ver.0

PAGE

20 OF 29

R2015-8006-O

A4(210 X 297)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	Ver.0	2018.4.9

10.0 MECHANICAL CHARACTERISTICS

10.1 Dimensional Requirements

FIGURE 6 (located in Appendix) shows mechanical outlines for the model MV230FHM-N40. Other parameters are shown in Table 5.

<Table 5. Dimensional Parameters>

Parameter	Specification	Unit
Dimensional outline	517.2(H) x 302.8(V) x12.3(D) typ.	mm
Weight	2100g (Typ.)	gram
Active area	509.184(H) × 286.416(V)	mm
Pixel pitch	0.2652(H)mm x 0.2652(V)mm	mm
Number of pixels	1920 (H) × 1080 (V) (1 pixel = R + G + B dots)	pixels
Back-light	Horizontal arranged, 1-LED Lighting Bar type	

10.2 Mounting

See FIGURE 5. (shown in Appendix)

10.3 Anti-Glare and Polarizer Hardness.

The surface of the LCD has an anti-glare coating to minimize reflection and a coating to reduce scratching.

10.4 Light Leakage

There shall not be visible light from the back-lighting system around the edges of the screen as seen from a distance 50cm from the screen with an overhead light level of 350lux.

SPEC. NUMBER S864-8D003	SPEC. TITLE B10 MV230FHM-N40 Product Specification Ver.0	PAGE 21 OF 29
----------------------------	---	------------------

BOE**PRODUCT GROUP**

REV

ISSUE DATE

TFT- LCD PRODUCT

Ver.0

2018.4.9

11.0 RELIABILITY TEST

The Reliability test items and its conditions are shown in below.

<Table 6. Reliability Test Parameters >

No	Test Items	Conditions	
1	High temperature storage test	Ta = 60 °C, 240 hrs	
2	Low temperature storage test	Ta = -20 °C, 240 hrs	
3	High temperature & high humidity operation test	Ta = 50 °C, 80%RH, 240hrs	
4	High temperature operation test	Ta = 50 °C, 240hrs	
5	Low temperature operation test	Ta = 0°C, 240hrs	
6	Thermal shock	Ta = -20 °C ↔ 60 °C (0.5 hr), 100 cycle	
7	Vibration test (non-operating)	Frequency	Random, 10 ~ 300 Hz, 30 min/Axis
		Gravity\AMP	1.5 Grms
		Period	X, Y, Z 30 min
8	Shock test (non-operating)	Gravity	50G
		Pulse width	11msec, sine wave
		Direction	± X, ± Y, ± Z Once for each
9	Electro-static discharge test	Air : 150 pF, 330Ω, 15 KV Contact : 150 pF, 330Ω, 8 KV	

SPEC. NUMBER

S864-8D003

SPEC. TITLE

B10 MV230FHM-N40 Product Specification Ver.0

PAGE

22 OF 29

R2015-8006-O

A4(210 X 297)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	Ver.0	2018.4.9

12.0 HANDLING & CAUTIONS

- (1) Cautions when taking out the module
 - Pick the pouch only, when taking out module from a shipping package.
- (2) Cautions for handling the module
 - As the electrostatic discharges may break the LCD module, handle the LCD module with care. Peel a protection sheet off from the LCD panel surface as slowly as possible.
 - As the LCD panel and back - light element are made from fragile glass material, impulse and pressure to the LCD module should be avoided.
 - As the surface of the polarizer is very soft and easily scratched, use a soft dry cloth without chemicals for cleaning.
 - Do not pull the interface connector in or out while the LCD module is operating.
 - Put the module display side down on a flat horizontal plane.
 - Handle connectors and cables with care.
- (3) Cautions for the operation
 - When the module is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the LCD panel would be damaged.
 - Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.
- (4) Cautions for the atmosphere
 - Dew drop atmosphere should be avoided.
 - Do not store and/or operate the LCD module in a high temperature and/or humidity atmosphere. Storage in an electro-conductive polymer packing pouch and under relatively low temperature atmosphere is recommended.
- (5) Cautions for the module characteristics
 - Do not apply fixed pattern data signal to the LCD module at product aging.
 - Applying fixed pattern for a long time may cause image sticking.
- (6) Other cautions
 - Do not disassemble and/or re-assemble LCD module.
 - Do not re-adjust variable resistor or switch etc.
 - When returning the module for repair or etc., Please pack the module not to be broken. We recommend to use the original shipping packages.

SPEC. NUMBER S864-8D003	SPEC. TITLE B10 MV230FHM-N40 Product Specification Ver.0	PAGE 23 OF 29
----------------------------	---	------------------

R2015-8006-O

A4(210 X 297)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	Ver.0	2018.4.9

13.0 PRODUCT SERIAL NUMBER

DP/N
XXXXXX

XXXX

CN-XXXXXX-XXXXX-XXX-XXXX

MV230FHM-N40 BA



XXXXXXXX-XXXX-XXXXXX



BOE

ECO
RoHS Compliant

UL US

MADE IN CHINA

Rev A00



MDL ID Naming Rule:

Digit	1	2	3	4	5	6				7						
Code	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x	x
Des.	1. Model Code GBN 2. Grade 3. Line 4. Year(2016:16, 2017:17, ...) 5. Month(1, 2, 3, ..., 9, X, Y, Z) 6. Model Extension Code (Last 4 Digits Of FG-Code) 7. Serial Number															

SPEC. NUMBER S864-8D003	SPEC. TITLE B10 MV230FHM-N40 Product Specification Ver.0	PAGE 24 OF 29
----------------------------	---	------------------

R2015-8006-O

A4(210 X 297)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	Ver.0	2018.4.9


14.0 Packing

14.1 Packing Order


Put 1 EPO bottom into the inner box.



Put each module into a PE bag.
Insert 10 Pcs MDL into each box



Put totally 12 boxes. Place paper corners and wrap film around the boxes. Pack with 4 packing belts.



Put 1 EPO cover in and seal the box.

SPEC. NUMBER S864-8D003	SPEC. TITLE B10 MV230FHM-N40 Product Specification Ver.0	PAGE 25 OF 29
----------------------------	---	------------------

R2015-8006-O

A4(210 X 297)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	Ver.0	2018.4.9

14.2 Packing Note

- Box Dimension : 613mm(W) × 306.5mm(L) × 399mm(H)
- Package Quantity in one Box : 10pcs

14.3 Box label

- Label Size : 100 mm (L) × 50 mm (W)
- Contents
 Model : MV230FHM-N40
 Q`ty : Module 10 Q`ty in one box
 Serial No. : Box Serial No.
 Date : Packing Date

BOE
FUZHOU BOE OPTOELECTRONICS
TECHNOLOGY Co.,LTD

MODEL: XXXXXXXX-XXX Q'TY: XXX

SERIAL NO: XXXXXXXXXXXXX DATE: XXXX.XX.XX






XXXXXXXXXXXXXXXX XXXX

Digit	1	2	3	4	5	6	7						
Code	x	x	x	x	x	x	x	x	x	x	x	x	x
Des.	1. Model Code GBN 2. Grade 3. Line 4. Year(2016:16, 2017:17, ...) 5. Month(1, 2, 3, ..., 9, X, Y, Z) 6. Revision Code 7. Serial Number												

SPEC. NUMBER S864-8D003	SPEC. TITLE B10 MV230FHM-N40 Product Specification Ver.0	PAGE 26 OF 29
----------------------------	---	------------------

R2015-8006-O

A4(210 X 297)



BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	Ver.0	2018.4.9

15.0 APPENDIX

Figure 1. Measurement Set Up





Figure 2. White Luminance and Uniformity Measurement Locations (9 points)



SPEC. NUMBER S864-8D003	SPEC. TITLE B10 MV230FHM-N40 Product Specification Ver.0	PAGE 27 OF 29
----------------------------	---	------------------

BOE

PRODUCT GROUP


REV

ISSUE DATE

TFT- LCD PRODUCT

Ver.0

2018.4.9


Figure 3. Response Time TestingSPEC. NUMBER
S864-8D003SPEC. TITLE
B10 MV230FHM-N40 Product Specification Ver.0PAGE
28 OF 29

R2015-8006-O

A4(210 X 297)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT- LCD PRODUCT	Ver.0	2018.4.9

Figure 5. TFT-LCD Module Outline Dimensions (Front view)



SPEC. NUMBER S864-8D003	SPEC. TITLE B10 MV230FHM-N40 Product Specification Ver.0	PAGE 29 OF 29
----------------------------	---	------------------

R2015-8006-O

A4(210 X 297)

