

**PROPRIETARY NOTE**

THIS SPECIFICATION IS THE PROPERTY OF BOE DT AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF BOE DT AND MUST BE RETURNED TO BOE DT UPON ITS REQUEST

TITLE : MV270FHM-N30**Product Specification****Rev. P1****BEIJING BOE Display TECHNOLOGY**

SPEC. NUMBER S8-65-8A-202	PRODUCT GROUP TFT LCD	Rev. P1	ISSUE DATE 2017.10.13	PAGE 1 OF 26
------------------------------	--------------------------	---------	--------------------------	-----------------

B2010-8002-A 1/3)

A4(210 X 297)

2017.10.13

(●)Final specification

Oct.13.2017

2 OF 26

A4(210 X 297)

**BOE****PRODUCT GROUP**

REV

ISSUE DATE

TFT LCD PRODUCT

Rev. P1

2017.10.13

Contents

No.	Item	Page
1.0	General Description	4
2.0	Absolute Maximum Ratings	6
3.0	Electrical Specifications	7
4.0	Optical Specifications	8
5.0	Interface Connection	10
6.0	Signal Timing Specifications	14
7.0	Signal Timing Waveforms of Interface Signal	16
8.0	Input Signals, Display Colors & Gray Scale of Colors	18
9.0	Power Sequence	19
10.0	Mechanical Characteristics	20
11.0	Reliability Test	21
12.0	Handling& Cautions	22
13.0	Product Serial Number	23
14.0	Packing	24
15.0	Appendix	27

SPEC. NUMBER
S8-65-8A-202SPEC. TITLE
MV270FHM-N30 Product Specification Rev.P1PAGE
3 OF 26

B2010-8002-A 3/3)


A4(210 X 297)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	Rev. P1	2017.10.13

1.0 GENERAL DESCRIPTION

1.1 Introduction

MV270FHM-N30 is a color active matrix TFT LCD module using amorphous silicon TFT's (Thin Film Transistors) as an active switching devices. This module has a 27 inch diagonally measured active area with FHD resolutions (1920 horizontal by 1080 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical stripe and this module can display 16.7M colors. The TFT-LCD panel used for this module is adapted for a low reflection and higher color type.



1.2 Features

- LVDS Interface with 2 pixel / clock
- High-speed response
- 0.5t Glass
- 6-bit (Hi-FRC) color depth, display 16. 7M colors
- Incorporated edge type back-light (One Light Bar)
- High luminance and contrast ratio, low reflection and wide viewing angle
- DE (Data Enable) only
- RoHS/Halogen Free
- ES 7.0 compliant
- Gamma Correction
- Reverse type

SPEC. NUMBER S8-65-8A-202	SPEC. TITLE MV270FHM-N30 Product Specification Rev.P1	PAGE 4 OF 26
-------------------------------------	---	------------------------

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	Rev. P1	2017.10.13

1.3 Application

- Desktop Type of PC & Workstation Use
- Slim-Size Display for Stand-alone Monitor
- Display Terminals for Control System
- Monitors for Process Controller

1.4 General Specification

The followings are general specifications at the model MV270FHM-N30.

<Table 1. General Specifications>

Parameter	Specification	Unit	Remarks
Active area	597.888(H) × 336.314(V)	mm	
Number of pixels	1920(H) × 1080(V)	pixels	
Pixel pitch	0.3114(H) x 0.3114(V)	mm	
Pixel arrangement	RGB Vertical stripe	-	
Display colors	16.7M	colors	
Display mode	Normally Black	-	
Dimensional outline	607.1(H) x 354.1(V) × 9.0(D) typ	mm	Detail refer to drawing
Weight	3.2	Kg	
Surface Treatment	Anti-glare, 3H	-	
Back-light	Horizontal arranged, 1-LED Lighting Bar type	-	

SPEC. NUMBER S8-65-8A-202	SPEC. TITLE MV270FHM-N30 Product Specification Rev.P1	PAGE 5 OF 26
------------------------------	--	-----------------

B2010-8002-A 3/3)

A4(210 X 297)

BOE**PRODUCT GROUP**

REV

ISSUE DATE

TFT LCD PRODUCT

Rev. P1

2017.10.13

2.0 ABSOLUTE MAXIMUM RATINGS

The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit. The operational and non-operational maximum voltage and current values are listed in Table 2.


< Table 2. Absolute Maximum Ratings>

[VSS=GND=0V]

Parameter	Symbol	Min.	Max.	Unit	Remarks
Power Supply Voltage	V_{DD}	-0.3	6.0	V	Ta = 25 °C
Logic Supply Voltage	V_{IN}	VSS-0.3	$V_{DD}+0.3$	V	
Operating Temperature	T_{OP}	0	+50	°C	1)
Storage Temperature	T_{ST}	-20	+60	°C	1)

Note : 1) Temperature and relative humidity range are shown in the figure below.

Wet bulb temperature should be 39 °C max. and no condensation of water.



SPEC. NUMBER
S8-65-8A-202

SPEC. TITLE
MV270FHM-N30 Product Specification Rev.P1

PAGE
6 OF 26

B2010-8002-A 3/3)

A4(210 X 297)



BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	Rev. P1	2017.10.13

3.0 ELECTRICAL SPECIFICATIONS

3.1 Electrical Specifications

< Table 3. Electrical specifications >

[Ta =25±2 °C]


Parameter		Min.	Typ.	Max.	Unit	Remarks
Power Supply Voltage	V _{DD}	4.5	5.0	5.5	V	Note1
Power Supply Current	I _{DD}	-	700	1100	mA	
In-Rush Current	I _{RUSH}	-	2.0	3	A	Note 2
Permissible Input Ripple Voltage	V _{RF}	-	-	300	mV	V _{DD} = 5.0V
High Level Differential Input Threshold Voltage	V _{IH}	-	-	+100	mV	
Low Level Differential Input Threshold Voltage	V _{IL}	-100	-	-	mV	
Differential input voltage	V _{ID}	200	-	600	mV	
Differential input common mode voltage	V _{cm}	1.0	1.2	1.5		V _{IH} =100mV, V _{IL} =-100mV
LED Voltage	V _L	2.8	3.0	3.2	V	
LED Channel Voltage	V _L	50.4	54	57.6	V	
LED Channel Current	I _L	-	57	-	mA	
LED Lifetime		30,000	-	-	Hrs	I _L =57 mA
Power Consumption	P _D		3.5	5.5	W	75Hz
	P _{BL}	-	12.31	13.13	W	I _L =57mA, Note 3
	P _{total}	-	15.81	18.63	W	

Notes : 1. The supply voltage is measured and specified at the interface connector of LCM.

The current draw and power consumption specified is for VDD=5.0V, Frame rate=75Hz. Test Pattern of power supply current

a) Typ : Color Bar pattern

b) Max : Vertical Subline pattern



2. Duration of rush current is about 2 ms and rising time of VDD is 520 μs ± 20 %

3. Calculated value for reference (V_L × I_L) × 4(channel) excluding driver loss. (LED Light bar: 18S4P)

SPEC. NUMBER S8-65-8A-202	SPEC. TITLE MV270FHM-N30 Product Specification Rev.P1	PAGE 7 OF 26
------------------------------	--	-----------------

B2010-8002-A 3/3)

A4(210 X 297)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	Rev. P1	2017.10.13

Parameter		Min.	Typ.	Max.	Unit	Remarks
LED Light Bar Input Voltage Per Input Pin	V _{PIN}	50.4	54	57.6	V	Duty 100%
LED Light Bar Input Current Per Input Pin	I _{PIN}	-	57	-	mA	Note1,2,
LED Power Consumption	P _{BL}	-	12.31	13.13	W	Note 3
LED Life-Time	-	30,000	-		Hrs	Note 4

LED bar consists of 72LED packages,4 strings(parallel)*18packages(serial)

Note1: There are one light bar ,and the specified current is input LED chip 100% duty current

Note2: The sense current of each input pin is 57mA

Note3: $P_{BL}=4 \text{ Input pins} \times V_{PIN} \times I_{PIN}$

Note4: The lifetime is determined as the time at which luminance of LED become 50% of the initial brightness or not normal lighting at I_{PIN}=57mA on condition of continuous operating at 25 ± 2 °C

SPEC. NUMBER S8-65-8A-202	SPEC. TITLE MV270FHM-N30 Product Specification Rev.P1	PAGE 8 OF 26
------------------------------	--	-----------------

B2010-8002-A 3/3)

A4(210 X 297)



BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	Rev. P1	2017.10.13

4.0 OPTICAL SPECIFICATION

4.1 Overview

The test of Optical specifications shall be measured in a dark room (ambient luminance ≤ 1 lux and temperature = $25 \pm 2^\circ\text{C}$) with the equipment of Luminance meter system (Goniometer system and TOPCONE PR730) and test unit shall be located at an approximate distance 50cm from the LCD surface at a viewing angle of θ and Φ equal to 0° . We refer to $\theta_{0=0}$ ($=\theta_3$) as the 3 o'clock direction (the "right"), $\theta_{0=90}$ ($=\theta_{12}$) as the 12 o'clock direction ("upward"), $\theta_{0=180}$ ($=\theta_9$) as the 9 o'clock direction ("left") and $\theta_{0=270}$ ($=\theta_6$) as the 6 o'clock direction ("bottom"). While scanning θ and/or Φ , the center of the measuring spot on the Display surface shall stay fixed. The measurement shall be executed after 30 minutes warm-up period. VDD shall be 5.0V $\pm$ 10% at 25°C . Optimum viewing angle direction is 6 o'clock.

4.2 Optical Specifications

[VDD = 5.0V, Frame rate = 60Hz, Clock = 74.25MHz, $I_{BL} = 160\text{mA}$, $T_a = 25 \pm 2^\circ\text{C}$]

< Table 4. Module Optical >

Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Viewing Angle range	Horizontal	Θ_3	CR > 10	85	89	-	Deg.	Note 1
		Θ_9		85	89	-	Deg.	
	Vertical	Θ_{12}		85	89	-	Deg.	
		Θ_6		85	89	-	Deg.	
Luminance Contrast ratio		CR	$\Theta = 0^\circ$ (Center) Normal Viewing Angle	700	1000			Note 2
Luminance of White		Y_w		200	250	-	cd/m ²	Note 3
White luminance uniformity		ΔY		75	-	-	%	Note 4
Reproduction of color	White	W_x		0.283	0.313	0.343	-	Note 5
		W_y		0.299	0.329	0.359	-	
	Red	R_x		0.615	0.645	0.675	-	
		R_y		0.307	0.337	0.367	-	
	Green	G_x		0.283	0.313	0.343	-	
		G_y		0.604	0.634	0.664	-	
	Blue	B_x		0.122	0.152	0.182	-	
		B_y		0.014	0.044	0.074	-	
	Color Gamut		NTSC	-	72	-	%	
Response Time	GTG	T_g			14	20	ms	Note 6
Cross Talk		CT		-	-	2.0	%	Note 7

SPEC. NUMBER S8-65-8A-202	SPEC. TITLE MV270FHM-N30 Product Specification Rev.P1	PAGE 9 OF 26
------------------------------	--	-----------------

B2010-8002-A 3/3)

A4(210 X 297)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	Rev. P1	2017.10.13

Note :

1. Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface.
2. Contrast measurements shall be made at viewing angle of $\theta = 0^\circ$ and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state. (See FIGURE 1 shown in Appendix) Luminance Contrast Ratio (CR) is defined mathematically.

$$CR = \frac{\text{Luminance when displaying a white raster}}{\text{Luminance when displaying a black raster}}$$

3. Center Luminance of white is defined as the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display.
4. The White luminance uniformity on LCD surface is then expressed as :
 $\Delta Y = (\text{Minimum Luminance of 9points} / \text{Maximum Luminance of 9points}) * 100$
 (See FIGURE 2 shown in Appendix).
5. The color chromaticity coordinates specified in Table 5. shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel.
6. Response time T_g is the average time required for display transition by switching the input signal as below table and is based on Frame rate $f_V = 60\text{Hz}$ to optimize.
 Each time in below table is defined as appendix Figure 3 and shall be measured by switching the input signal for "any level of gray(bright)" and "any level of gray(dark)".

Measured Response Time	0	15	31	47	63	79	95	111	127	143	159	175	191	207	223	239	255
0																	
15																	
31																	
47																	
63																	
79																	
95																	
111																	
127																	
143																	
159																	
175																	
191																	
207																	
223																	
239																	
255																	

7. Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (Y_A) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (Y_B) of that same area when any adjacent area is driven dark. (See FIGURE 4 shown in Appendix).

SPEC. NUMBER S8-65-8A-202	SPEC. TITLE MV270FHM-N30 Product Specification Rev.P1	PAGE 10 OF 26
-------------------------------------	---	-------------------------

B2010-8002-A 3/3)

A4(210 X 297)

	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	Rev. P1	2017.10.13

5.0 INTERFACE CONNECTION.

5.1 Electrical Interface Connection

5.1.1 LED Light Bar

-LED connector : 10035WS-H06D manufactured by YEONHO

< Table 5. LED Light Bar>

Pin No	Symbol	Description
1	IRLED1	LED current sense for string1
2	IRLED2	LED current sense for string2
3	VLED	LED power supply
4	VLED	LED power supply
5	IRLED3	LED current sense for string3
6	IRLED4	LED current sense for string4

SPEC. NUMBER S8-65-8A-202	SPEC. TITLE MV270FHM-N30 Product Specification Rev.P1	PAGE 11 OF 26
------------------------------	--	------------------

B2010-8002-A 3/3) A4(210 X 297)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	Rev. P1	2017.10.13

5.2 Electrical Interface Connection

- CN11 Module Side Connector : UJU IS100-L300-C23
User Side Connector : JAE FI-X30H or Equivalent

Pin No	Symbol	Function	Remark
1	RXO0-	Negative Transmission data of Pixel 0 (ODD)	
2	RXO0+	Positive Transmission data of Pixel 0 (ODD)	
3	RXO1-	Negative Transmission data of Pixel 1 (ODD)	
4	RXO1+	Positive Transmission data of Pixel 1 (ODD)	
5	RXO2-	Negative Transmission data of Pixel 2 (ODD)	
6	RXO2+	Positive Transmission data of Pixel 2 (ODD)	
7	BIST	Bist function	Note1
8	RXOC-	Negative Transmission Clock (ODD)	
9	RXOC+	Positive Transmission Clock (ODD)	
10	RXO3-	Negative Transmission data of Pixel 3 (ODD)	
11	RXO3+	Positive Transmission data of Pixel 3 (ODD)	
12	RXE0-	Negative Transmission data of Pixel 0 (EVEN)	
13	RXE0+	Positive Transmission data of Pixel 0 (EVEN)	
14	GND	Power Ground	
15	RXE1-	Negative Transmission data of Pixel 1 (EVEN)	
16	RXE1+	Positive Transmission data of Pixel 1 (EVEN)	
17	GNG	Power Ground	
18	RXE2-	Negative Transmission data of Pixel 2 (EVEN)	
19	RXE2+	Positive Transmission data of Pixel 2 (EVEN)	
20	RXEC-	Negative Transmission Clock (EVEN)	
21	RXEC+	Positive Transmission Clock (EVEN)	
22	RXE3-	Negative Transmission data of Pixel 3 (EVEN)	
23	RXE3+	Positive Transmission data of Pixel 3 (EVEN)	
24	GND	Power Ground	Note 2
25	SCL	*Reserved for LCD manufacturer's(SCL)	
26	SDA	*Reserved for LCD manufacturer's(SDA)	
27	NC		
28	VDD	Power Supply: +5V	
29	VDD		
30	VDD		

Note 1 : H: White-Black-Red-Green-Blue Pattern Aging, L:Black pattern,when no LVDS signal

Note2: This pin should be connected with GND.

SPEC. NUMBER S8-65-8A-202	SPEC. TITLE MV270FHM-N30 Product Specification Rev.P1	PAGE 12 OF 26
-------------------------------------	---	-------------------------

B2010-8002-A 3/3)

A4(210 X 297)

BOE

PRODUCT GROUP

REV


ISSUE DATE

TFT LCD PRODUCT

Rev. P1

2017.10.13

5.2 Data Input Format



5.3 Back-light Interface Connection

-LED connector : 10035WS-H06D manufactured by YEONHO

Pin	Function
1	Channel 1 Current Feedback
2	Channel 2 Current Feedback
3	LED Power Supply
4	LED Power Supply
5	Channel3 Current Feedback
6	Channel4 Current Feedback

SPEC. NUMBER
S8-65-8A-202

SPEC. TITLE
MV270FHM-N30 Product Specification Rev.P1

PAGE
13 OF 26

B2010-8002-A 3/3)

A4(210 X 297)

**BOE****PRODUCT GROUP**

REV

ISSUE DATE

TFT LCD PRODUCT

Rev. P1

2017.10.13

6.0 SIGNAL TIMING SPECIFICATION

6.1 The MV270FHM-N30 is operated by the DE only.

Item	Symbols		Min	Typ	Max	Unit	Note
DCLK	Period	tCLK	10.78	13.47	16.84	ns	
	Frequency	-	59.4	74.25	92.82	MHz	
Hsync	Period	tHP	1050	1100	1120	tCLK	
	Horizontal Valid	tHV	960	960	960	tCLK	
	Horizontal Blank	tHB	90	140	160	tCLK	
	Frequency	fH	56.3	67.5	84.4	KHz	
Vsync	Period	tVP	1110	1125	1251	tHP	
	Vertical Valid	tVV	1080	1080	1080	tHP	
	Vertical Blank	tVB	30	45	171	tHP	
	Frequency	fV	48	60	75	Hz	
LVDS Receiver clock	Input spread spectrum ratio	SSr	-3	-	+3	%	

Note 1 : This DCLK range at last line of V-blanking should be set in 0~987.

SPEC. NUMBER
S8-65-8A-202SPEC. TITLE
MV270FHM-N30 Product Specification Rev.P1PAGE
14 OF 26

B2010-8002-A 3/3)

A4(210 X 297)

**BOE****PRODUCT GROUP**

REV

ISSUE DATE

TFT LCD PRODUCT

Rev. P1


2017.10.13

6.2 LVDS Rx Interface Timing Parameter

The specification of the LVDS Rx interface timing parameter is shown in Table 4.

<Table 4. LVDS Rx Interface Timing Specification>

Item	Symbol	Min	Typ	Max	Unit	Remark
CLKIN Period	tRCIP	10.78	13.47	16.84	nsec	
Input Data 0	tRIP1	-0.4	0.0	+0.4	nsec	
Input Data 1	tRIP0	tRCIP/7-0.4	tRCIP/7	tRCIP/7+0.4	nsec	
Input Data 2	tRIP6	$2 \times \text{tRCIP}/7-0.4$	$2 \times \text{tRCIP}/7$	$2 \times \text{tRCIP}/7+0.4$	nsec	
Input Data 3	tRIP5	$3 \times \text{tRCIP}/7-0.4$	$3 \times \text{tRCIP}/7$	$3 \times \text{tRCIP}/7+0.4$	nsec	
Input Data 4	tRIP4	$4 \times \text{tRCIP}/7-0.4$	$4 \times \text{tRCIP}/7$	$4 \times \text{tRCIP}/7+0.4$	nsec	
Input Data 5	tRIP3	$5 \times \text{tRCIP}/7-0.4$	$5 \times \text{tRCIP}/7$	$5 \times \text{tRCIP}/7+0.4$	nsec	
Input Data 6	tRIP2	$6 \times \text{tRCIP}/7-0.4$	$6 \times \text{tRCIP}/7$	$6 \times \text{tRCIP}/7+0.4$	nsec	



* $V_{diff} = (RXZ+) - (RXZ-), \dots, (RXCLK+) - (RXCLK-)$

SPEC. NUMBER
S8-65-8A-202

SPEC. TITLE
MV270FHM-N30 Product Specification Rev.P1

PAGE
15 OF 26

B2010-8002-A 3/3)

A4(210 X 297)

**BOE****PRODUCT GROUP**


REV

ISSUE DATE


TFT LCD PRODUCT

Rev. P1

2017.10.13

7.0 SIGNAL TIMING WAVEFORMS OF INTERFACE SIGNAL**7.1 Sync Timing Waveforms**

- 1) Need over 3 H-sync during V-Sync Low
- 2) Fix H-Sync width from V-Sync falling edge to first rising edge

7.2 Vertical Timing Waveforms

SPEC. NUMBER

S8-65-8A-202

SPEC. TITLE

MV270FHM-N30 Product Specification Rev.P1

PAGE

16 OF 26

B2010-8002-A 3/3)

A4(210 X 297)

BOE**PRODUCT GROUP**



REV

ISSUE DATE

TFT LCD PRODUCT

Rev. P1

2017.10.13

7.3 Horizontal Timing WaveformsSPEC. NUMBER
S8-65-8A-202SPEC. TITLE
MV270FHM-N30 Product Specification Rev.P1PAGE
17 OF 26

B2010-8002-A 3/3)

A4(210 X 297)

**BOE****PRODUCT GROUP**

REV

ISSUE DATE

TFT LCD PRODUCT

Rev. P1

2017.10.13

8.0 INPUT SIGNALS, BASIC DISPLAY COLORS & GRAY SCALE OF COLORS

Color & Gray Scale		RED DATA								GREEN DATA								BLUE DATA							
		R7	R6	R5	R4	R3	R2	R1	R0	G7	G6	G5	G4	G3	G2	G1	G0	B7	B6	B5	B4	B3	B2	B1	B0
Basic Colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Green	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	Cyan	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
	Red	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Magenta	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Gray Scale of RED	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Darker	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	↑								↑								↑							
	▽	↓								↓								↓							
	Brighter	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	▽	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Gray Scale of GREEN	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0
	△	↑								↑								↑							
	▽	↓								↓								↓							
	Brighter	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0	0
	▽	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0
	Green	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	0	0	0	0	0	0	0	0
Gray Scale of BLUE	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0
	△	↑								↑								↑							
	▽	↓								↓								↓							
	Brighter	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	1
	▽	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1
Gray Scale of WHITE	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1
	Darker	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0	0	0	0	0	0	1	0	0
	△	↑								↑								↑							
	▽	↓								↓								↓							
	Brighter	1	1	1	1	1	1	0	1	1	1	1	1	1	1	0	1	1	1	1	1	1	1	0	1
	▽	1	1	1	1	1	1	1	0	1	1	1	1	1	1	0	1	1	1	1	1	1	1	1	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

SPEC. NUMBER

S8-65-8A-202

SPEC. TITLE

MV270FHM-N30 Product Specification Rev.P1

PAGE

18 OF 26


B2010-8002-A 3/3)

A4(210 X 297)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	Rev. P1	2017.10.13

9.0 POWER SEQUENCE

To prevent a latch-up or DC operation of the LCD module, the power on/off sequence shall be as shown in below



- $0.5 \text{ ms} \leq T1 \leq 10 \text{ ms}$
- $0 \leq T2 \leq 50 \text{ ms}$
- $0 \leq T3 \leq 50 \text{ ms}$
- $1 \text{ sec} \leq T4$
- $200 \text{ ms} \leq T5$
- $200 \text{ ms} \leq T6$

Notes:

1. When the power supply VDD is 0V, keep the level of input signals on the low or keep high impedance.
2. Do not keep the interface signal high impedance when power is on.
3. Back Light must be turn on after power for logic and interface signal are valid.
4. T7 decreases smoothly, there is none re-bouncing voltage.

SPEC. NUMBER S8-65-8A-202	SPEC. TITLE MV270FHM-N30 Product Specification Rev.P1	PAGE 19 OF 26
------------------------------	--	------------------

BOE**PRODUCT GROUP**

REV

ISSUE DATE

TFT LCD PRODUCT

Rev. P1

2017.10.13

10.0 MECHANICAL CHARACTERISTICS**10.1 Dimensional Requirements**

FIGURE 5 (located in Appendix) shows mechanical outlines for the model MV270FHM-N30. Other parameters are shown in Table 8.

<Table 8. Dimensional Parameters>

Parameter	Specification	Unit
Dimensional outline	607.1(H) × 354.1(V) × 12.7(D) typ.	mm
Weight	3.2	Kg
Active area	597.888(H) × 336.312(V)	mm
Pixel pitch	0.3114(H) x 0.3114(V)	mm
Number of pixels	1920(H)×1080(V) (1 pixel = R + G + B dots)	pixels
Back-light	Down edge side 1-LED Light bar Type	

10.2 Mounting

See FIGURE 5 . (shown in Appendix)

10.3 Anti-Glare and Polarizer Hardness.

The surface of the LCD has an anti-glare coating to minimize reflection and a coating to reduce scratching.

10.4 Light Leakage

There shall not be visible light from the back-lighting system around the edges of the screen as seen from a distance 50cm from the screen with an overhead light level of 350lux.

SPEC. NUMBER
S8-65-8A-202

SPEC. TITLE
MV270FHM-N30 Product Specification Rev.P1

PAGE
20 OF 26

B2010-8002-A 3/3)

A4(210 X 297)

**BOE****PRODUCT GROUP**

REV

ISSUE DATE

TFT LCD PRODUCT

Rev. P1

2017.10.13

11.0 RELIABILITY TEST

The Reliability test items and its conditions are shown in below.

<Table 9 Reliability Test Parameters >

No	Test Items	Conditions	
1	High temperature storage test	Ta = 60 °C , 240 hrs	
2	Low temperature storage test	Ta = -20 °C , 240 hrs	
3	High temperature & high humidity operation test	Ta = 50 °C , 80%RH, 240hrs	
4	High temperature operation test	Ta = 50 °C , 240hrs	
5	Low temperature operation test	Ta = 0°C , 240hrs	
6	Thermal shock	Ta = -20 °C ↔ 60 °C (0.5 hr), 100 cycle	
7	Vibration test (non-operating)	Frequency	Random, 10 ~ 300 Hz, 30 min/Axis
		Gravity / AMP	1.5 Grms
		Period	X, Y, Z 30 min
8	Shock test (non-operating)	Gravity	50G
		Pulse width	11msec, sine wave
		Direction	± X, ± Y, ± Z Once for each
9	Electro-static discharge test	Air : 150 pF, 330Ω, 15 KV Contact : 150 pF, 330Ω, 8 KV	
10	Altitude test	Non Operating: 40000 ft, -10°C / 24 Hr, 25°C / 24 Hr, -10°C / 24 Hr	
		Operating: 15000 ft, 0°C / 24 Hr, 25°C / 24 Hr, 50°C / 24 Hr	

SPEC. NUMBER

S8-65-8A-202

SPEC. TITLE

MV270FHM-N30 Product Specification Rev.P1

PAGE

21 OF 26

B2010-8002-A 3/3)

A4(210 X 297)



	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	Rev. P1	2017.10.13

12.0 HANDLING & CAUTIONS

- (1) Cautions when taking out the module
 - Pick the pouch only, when taking out module from a shipping package.
- (2) Cautions for handling the module
 - As the electrostatic discharges may break the LCD module, handle the LCD module with care. Peel a protection sheet off from the LCD panel surface as slowly as possible.
 - As the LCD panel and back - light element are made from fragile glass material, impulse and pressure to the LCD module should be avoided.
 - As the surface of the polarizer is very soft and easily scratched, use a soft dry cloth without chemicals for cleaning.
 - Do not pull the interface connector in or out while the LCD module is operating.
 - Put the module display side down on a flat horizontal plane.
 - Handle connectors and cables with care.
- (3) Cautions for the operation
 - When the module is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the LCD panel would be damaged.
 - Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.
- (4) Cautions for the atmosphere
 - Dew drop atmosphere should be avoided.
 - Do not store and/or operate the LCD module in a high temperature and/or humidity atmosphere. Storage in an electro-conductive polymer packing pouch and under relatively low temperature atmosphere is recommended.
- (5) Cautions for the module characteristics
 - Do not apply fixed pattern data signal to the LCD module at product aging.
 - Applying fixed pattern for a long time may cause image sticking.
- (6) Other cautions
 - Do not disassemble and/or re-assemble LCD module.
 - Do not re-adjust variable resistor or switch etc.
 - When returning the module for repair or etc., Please pack the module not to be broken. We recommend to use the original shipping packages.

SPEC. NUMBER S8-65-8A-202	SPEC. TITLE MV270FHM-N30 Product Specification Rev.P1	PAGE 22 OF 26
------------------------------	--	------------------

B2010-8002-A 3/3)

A4(210 X 297)

	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	Rev. P1	2017.10.13

13.0 PRODUCT SERIAL NUMBER



1	2	3	4	5	6	7
X X	X	X	X X	X	X X X X	X X X X X X X

1. Control Number

2. Rank / Grade

3. Line Classification

4. Year (2001 : 01, 2002 : 02, ...)

5. Month (1,2,3, ... , 9, X, Y, Z)

6. Internal Use

7. Serial Number

SPEC. NUMBER S8-65-8A-202	SPEC. TITLE MV270FHM-N30 Product Specification Rev.P1	PAGE 23 OF 26
------------------------------	--	------------------


B2010-8002-A 3/3)

A4(210 X 297)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	Rev. P1	2017.10.13

14.0 Packing

14.1 Packing Order




Put 1 EPO bottom into the inner box.





Put each module into a PE bag.
Insert 8 Pcs MDL into each box.



Put 1 EPO cover in and seal the box.



Place paper corners and wrap film around the boxes.
Pack with 4 packing belts.



Put the boxes on the pallet (12 boxes per pallet)

SPEC. NUMBER S8-65-8A-202	SPEC. TITLE MV270FHM-N30 Product Specification Rev.P1	PAGE 24 OF 26
------------------------------	--	------------------

B2010-8002-A 3/3)

A4(210 X 297)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	Rev. P1	2017.10.13

14.3 Packing Specification and Note

Item	Specification			Remark
	Q'ty	Dimension(mm)	Weight (kg)	
MDL	1	607.1(H)*345.1(V)*12.7(D) typ.	3.2	-
Cushion	-	-	-	-
Box	1	675(L)×271(W)×443(H)	0.669	without Panel & cushion
Packing Box	8pcs/Box	687(L)×283(W)×455(H)	26.2	with panel & cushion
Pallet	1	1380(L)×900(W)×130(H)	18.5	-
Packing Pallet	12Box/Pallet	1380(L)×900(W)×130(H)	348.4	-

14.3 Box label

- Label Size : 110 mm (L) × 55 mm (W)
- Contents
 - Model : MV270FHM-N30
 - Q'ty : Module 8 Q'ty in one box
 - Serial No. : Box Serial No. See next page for detail description.
 - Date : Packing Date
 - FG Code : FG Code of Product

BEIJING BOE DISPLAY TECHNOLOGY CO., LTD.

MODEL : MV270FHM-N30 **Q'TY :** 8

SERIAL NO. : 00000000000000 **DATE :** 20XX.X.XX



• QAA0330000268 •

(5940)



(QA)

00	0	00	0	0	000000
Type	Grade	Year	Month	ITEM-CODE	Serial_no

Internal Use

RoHS Mark

SPEC. NUMBER S8-65-8A-202	SPEC. TITLE MV270FHM-N30 Product Specification Rev.P1	PAGE OF 26
-------------------------------------	---	----------------------

B2010-8002-A 3/3)

A4(210 X 297)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	Rev. P1	2017.10.13

15.0 APPENDIX

Figure 1. Measurement Set Up





Figure 2. White Luminance and Uniformity Measurement Locations (9 points)



SPEC. NUMBER S8-65-8A-202	SPEC. TITLE MV270FHM-N30 Product Specification Rev.P1	PAGE 26 OF 26
------------------------------	--	------------------

B2010-8002-A 3/3)

A4(210 X 297)

BOE

PRODUCT GROUP

REV

ISSUE DATE

TFT LCD PRODUCT

Rev. P1

2017.10.13

Figure 3. Response Time Testing





Figure 4. Cross Modulation Test Description



$$\text{Cross-Talk (\%)} = \left| \frac{Y_B - Y_A}{Y_A} \right| \times 100$$

Where: Y_A = Initial luminance of measured area (cd/m^2)

Y_B = Subsequent luminance of measured area (cd/m^2)

The location measured will be exactly the same in both patterns

SPEC. NUMBER
S8-65-8A-202

SPEC. TITLE
MV270FHM-N30 Product Specification Rev.P1


PAGE
27 OF 26

B2010-8002-A 3/3)

A4(210 X 297)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	Rev. P1	2017.10.13




Figure 5. TFT-LCD Module Outline Dimensions (Front view)



SPEC. NUMBER S8-65-8A-202	SPEC. TITLE MV270FHM-N30 Product Specification Rev.P1	PAGE 28 OF 26
------------------------------	--	------------------

B2010-8002-A 3/3)

A4(210 X 297)

	PRODUCT GROUP	REV	ISSUE DATE
	TFT LCD PRODUCT	Rev. P1	2017.10.13
Figure 6. TFT-LCD Module Outline Dimensions (Rear view)  NOTE: 1. I/F CONNECTOR SPECIFICATION UJU IS100-L300-C23 2. LED CONNECTOR SPECIFICATION YEONHO 1003SWS-H06D 3. USER MOUNTING TORQUE SPEC : 3 ~ 4 kgf·cm 4. Tilt and portial disposition tolerance of display area as following (1) Y-direction: $-0.45 \leq A \leq 0.45$, $-0.45 \leq B \leq 0.45$ (2) X-direction: $-0.45 \leq C \leq 0.45$, $-0.45 \leq D \leq 0.45$ 5. Unspecified tolerances to be ± 0.5 6. The COF ared is weak & sensive, so please don't press the COF Area Section A-A Scale 2:1  Section C-C Scale 2:1 			
SPEC. NUMBER S8-65-8A-202	SPEC. TITLE MV270FHM-N30 Product Specification Rev.P1		PAGE 29 OF 26

B2010-8002-A 3/3)

A4(210 X 297)