



# **INNOLUX DISPLAY CORPORATION**

## **SPECIFICATION**

**Customer:** \_\_\_\_\_

**Model Name:** NE070NB-04F

**Date:** 2018/4/20

**Version:** 08

☐ **Preliminary Specification**

☒ **Final Specification**

| Remark                |
|-----------------------|
| 7DD FOG (FPC:47.51mm) |

**For Customer's Acceptance**

| Approved by | Comment |
|-------------|---------|
|             |         |

| Approved by             | Reviewed by                           | Prepared by |
|-------------------------|---------------------------------------|-------------|
| Henry Chien<br>Cs chang | Sunny Sun<br>Cc01 chen<br>Wenguo deng | Yali.huo    |



CHIMEI INNOLUX copyright 2004  
All rights reserved,  
Copying forbidden.

## Record of Revision

| Version       | Revise Date | Page  | Content                                                                           |
|---------------|-------------|-------|-----------------------------------------------------------------------------------|
| Final-spec.01 | 2010/01/19  | All   | Initial Release                                                                   |
| Final-spec.02 | 2010/03/22  | 1     | Add the Value of Weight                                                           |
|               |             | 17    | Add Packaging Material Table & Packaging Quantity                                 |
|               |             | 18    | Add Packaging Drawing                                                             |
| Final-spec.03 | 2010/04/28  | All   | Add the Model Name, Spec NO., and Update the Logo                                 |
| Final-spec.04 | 2010/11/03  | 6     | Modify $V_{COM}$ values and add note 4                                            |
| Final-spec.05 | 2011/09/05  | 16    | Modify mechanical drawing from 1+2 to 1+1 IC                                      |
|               |             | 17    | Modify Packaging Material Table & Packaging                                       |
| Final-spec.06 | 2011/12/15  | 16    | Update mechanical drawing: the size of Gate IC                                    |
| Final-spec.07 | 2016/09/18  | 1     | Add IC & Driving methods                                                          |
|               |             | 7~11  | Add the Value of min& typ.&max& notes                                             |
|               |             | 13    | Add notes                                                                         |
|               |             | 14    | Add notes&ESD                                                                     |
|               |             | 16    | Update mechanical drawing                                                         |
|               |             | 17/18 | Update Package Drawing                                                            |
| Final-spec.08 | 2018/03/20  |       | Add T2 Cell as 2nd source & change module name from AT070TN90 V.1 to NE070NB-04F. |
|               |             | 1     | Update the Display Color& power consumption                                       |
|               |             | 6~8   | Update the Value of $V_{GH}$ & $V_{GL}$ & $V_{COM}$                               |
|               |             | 11~13 | Update the Transmittance and notes                                                |
|               |             | 16~18 | Update the Package Drawing                                                        |



## Contents

|                                                  |    |
|--------------------------------------------------|----|
| 1. General Specifications .....                  | 1  |
| 2. Pin Assignment .....                          | 2  |
| 3. Operation Specifications .....                | 5  |
| 3.1. Absolute Maximum Ratings .....              | 5  |
| 3.1.1. Typical Operation Conditions .....        | 6  |
| 3.1.2. Current Consumption .....                 | 7  |
| 3.2. Power Sequence .....                        | 7  |
| 3.3. Timing Characteristics .....                | 8  |
| 3.3.1. AC Electrical Characteristics .....       | 8  |
| 3.3.2. Input Clock and Data Timing Diagram ..... | 9  |
| 3.3.3. Timing .....                              | 9  |
| 3.3.4. Data Input Format .....                   | 10 |
| 4. Optical Specifications .....                  | 11 |
| 5. Reliability Test Items .....                  | 14 |
| 6. General Precautions .....                     | 15 |
| 6.1. Safety .....                                | 15 |
| 6.2. Handling .....                              | 15 |
| 6.3. Static Electricity .....                    | 15 |
| 6.4. Storage .....                               | 15 |
| 6.5. Cleaning .....                              | 15 |
| 7. Mechanical Drawing .....                      | 16 |
| 8. Package Drawing .....                         | 17 |
| 8.1. Packaging Material Table .....              | 17 |
| 8.2. Packaging Quantity .....                    | 17 |
| 8.3. Packaging Drawing .....                     | 18 |



## 1. General Specifications

| No. | Item                    | Specification                        | Remark |
|-----|-------------------------|--------------------------------------|--------|
| 1   | LCD size                | 7.0 inch(Diagonal)                   |        |
| 2   | Driver element          | a-Si TFT active matrix               |        |
| 3   | Resolution              | 800 × 3(RGB) × 480                   |        |
| 4   | Display mode            | Normally White, Transmissive         |        |
| 5   | Dot pitch               | 0.0642(W) × 0.1790(H) mm             |        |
| 6   | Active area             | 154.08(W) × 85.92(H) mm              |        |
| 7   | Panel size              | 162.5(W) × 96.62(H) × 1.43(D) mm     | Note 1 |
| 8   | Surface treatment       | Anti-Glare                           |        |
| 9   | Color arrangement       | RGB-stripe                           |        |
| 10  | Display Color           | 16.7M                                |        |
| 11  | Interface               | Digital, Parallel 8-bit RGB          |        |
| 12  | Panel power consumption | 0.240W (Typ.)                        |        |
| 13  | Weight                  | 46g(Typ.)                            |        |
| 14  | Source-IC<br>Gate-IC    | EK9713/ NT39419<br>EK73002 / NT52001 |        |
| 15  | Driving methods         | 1+2 dot                              |        |

Note 1: Refer to Mechanical Drawing.



## 2. Pin Assignment

FPC Connector is used for the module electronics interface. The recommended model is FH12A-50S-0.5SH manufactured by Hirose.

| Pin No. | Symbol            | I/O | Function                          | Remark |
|---------|-------------------|-----|-----------------------------------|--------|
| 1       | V <sub>LED+</sub> | P   | Power for LED backlight (Anode)   |        |
| 2       | V <sub>LED+</sub> | P   | Power for LED backlight (Anode)   |        |
| 3       | V <sub>LED-</sub> | P   | Power for LED backlight (Cathode) |        |
| 4       | V <sub>LED-</sub> | P   | Power for LED backlight (Cathode) |        |
| 5       | GND               | P   | Power ground                      |        |
| 6       | V <sub>COM</sub>  | I   | Common voltage                    |        |
| 7       | DV <sub>DD</sub>  | P   | Power for Digital Circuit         |        |
| 8       | MODE              | I   | DE/SYNC mode select               | Note 1 |
| 9       | DE                | I   | Data Input Enable                 |        |
| 10      | VS                | I   | Vertical Sync Input               |        |
| 11      | HS                | I   | Horizontal Sync Input             |        |
| 12      | B7                | I   | Blue data(MSB)                    |        |
| 13      | B6                | I   | Blue data                         |        |
| 14      | B5                | I   | Blue data                         |        |
| 15      | B4                | I   | Blue data                         |        |
| 16      | B3                | I   | Blue data                         |        |
| 17      | B2                | I   | Blue data                         |        |
| 18      | B1                | I   | Blue data                         | Note 2 |
| 19      | B0                | I   | Blue data(LSB)                    | Note 2 |
| 20      | G7                | I   | Green data(MSB)                   |        |
| 21      | G6                | I   | Green data                        |        |
| 22      | G5                | I   | Green data                        |        |
| 23      | G4                | I   | Green data                        |        |
| 24      | G3                | I   | Green data                        |        |
| 25      | G2                | I   | Green data                        |        |



|    |                  |   |                          |          |
|----|------------------|---|--------------------------|----------|
| 26 | G1               | I | Green data               | Note 2   |
| 27 | G0               | I | Green data(LSB)          | Note 2   |
| 28 | R7               | I | Red data(MSB)            |          |
| 29 | R6               | I | Red data                 |          |
| 30 | R5               | I | Red data                 |          |
| 31 | R4               | I | Red data                 |          |
| 32 | R3               | I | Red data                 |          |
| 33 | R2               | I | Red data                 |          |
| 34 | R1               | I | Red data                 | Note 2   |
| 35 | R0               | I | Red data(LSB)            | Note 2   |
| 36 | GND              | P | Power Ground             |          |
| 37 | DCLK             | I | Sample clock             | Note 3   |
| 38 | GND              | P | Power Ground             |          |
| 39 | L/R              | I | Left / right selection   | Note 4,5 |
| 40 | U/D              | I | Up/down selection        | Note 4,5 |
| 41 | V <sub>GH</sub>  | P | Gate ON Voltage          |          |
| 42 | V <sub>GL</sub>  | P | Gate OFF Voltage         |          |
| 43 | AV <sub>DD</sub> | P | Power for Analog Circuit |          |
| 44 | RESET            | I | Global reset pin.        | Note 6   |
| 45 | NC               | - | No connection            |          |
| 46 | V <sub>COM</sub> | I | Common Voltage           |          |
| 47 | DITHB            | I | Dithering function       | Note 7   |
| 48 | GND              | P | Power Ground             |          |
| 49 | NC               | - | No connection            |          |
| 50 | NC               | - | No connection            |          |

I: input, O: output, P: Power

Note 1: DE/SYNC mode select. Normally pull high.

When select DE mode, MODE="1", VS and HS must pull high.

When select SYNC mode, MODE= "0", DE must be grounded.


Note 2: When input 18 bits RGB data, the two low bits of R,G and B data must be grounded.

Note 3: Data shall be latched at the falling edge of DCLK.

Note 4: Selection of scanning mode

| Setting of scan control input |                  | Scanning direction        |
|-------------------------------|------------------|---------------------------|
| U/D                           | L/R              |                           |
| GND                           | DV <sub>DD</sub> | Up to down, left to right |
| DV <sub>DD</sub>              | GND              | Down to up, right to left |
| GND                           | GND              | Up to down, right to left |
| DV <sub>DD</sub>              | DV <sub>DD</sub> | Down to up, left to right |

Note 5: Definition of scanning direction.  
Refer to the figure as below:



Note 6: Global reset pin. Active low to enter reset state. Suggest to connect with an RC reset circuit for stability. Normally pull high.

Note 7: Dithering function enable control, normally pull high.  
When DITHB="1", Disable internal dithering function,  
When DITHB="0", Enable internal dithering function,

Note 8: Reserve for LED power input.



## 3. Operation Specifications

### 3.1. Absolute Maximum Ratings

(Note 1)

| Item                  | Symbol           | Values |      | Unit | Remark |
|-----------------------|------------------|--------|------|------|--------|
|                       |                  | Min.   | Max. |      |        |
| Power voltage         | DV <sub>DD</sub> | -0.3   | 5.0  | V    |        |
|                       | AV <sub>DD</sub> | 6.5    | 13.5 | V    |        |
|                       | V <sub>GH</sub>  | -0.3   | 40.0 | V    |        |
|                       | V <sub>GL</sub>  | -20.0  | 0.3  | V    |        |
| Operation Temperature | T <sub>OP</sub>  | -20    | 70   | °C   |        |
| Storage Temperature   | T <sub>ST</sub>  | -30    | 80   | °C   |        |

Note 1: The absolute maximum rating values of this product are not allowed to be exceeded at any times. Should a module be used with any of the absolute maximum ratings exceeded, the characteristics of the module may not be recovered, or in an extreme case, the module may be permanently destroyed.



## 3.1.1. Typical Operation Conditions

( Note 1)


| Item                     | Symbol           | Values               |        |                      | Unit | Remark |
|--------------------------|------------------|----------------------|--------|----------------------|------|--------|
|                          |                  | Min.                 | Typ.   | Max.                 |      |        |
| Power voltage            | DV <sub>DD</sub> | 3.0                  | 3.3    | 3.6                  | V    | Note 2 |
|                          | AV <sub>DD</sub> | 10.2                 | 10.4   | 10.6                 | V    |        |
|                          | V <sub>GH</sub>  | 14.5                 | 15     | 15.5                 | V    |        |
|                          | V <sub>GL</sub>  | -10.5                | -10    | -9.5                 | V    |        |
| Input signal voltage     | V <sub>COM</sub> | 3.54                 | (4.04) | 4.54                 | V    | Note 4 |
| Input logic high voltage | V <sub>IH</sub>  | 0.7 DV <sub>DD</sub> | /      | DV <sub>DD</sub>     | V    | Note 3 |
| Input logic low voltage  | V <sub>IL</sub>  | 0                    | /      | 0.3 DV <sub>DD</sub> | V    |        |

Note 1: Be sure to apply DV<sub>DD</sub> and V<sub>GL</sub> to the LCD first, and then apply V<sub>GH</sub>.

Note 2: DV<sub>DD</sub> setting should match the signals output voltage (refer to Note 3) of customer's system board.

Note 3: DCLK,HS,VS,RESET,U/D, L/R,DE,R0~R7,G0~G7,B0~B7,MODE,DITHB.

Note 4: Typical V<sub>COM</sub> is only a reference value. It must be optimized according to each LCM. Please use VR and base on below application circuit.




### 3.1.2. Current Consumption


| Item               | Symbol        | Values |      |      | Unit | Remark            |
|--------------------|---------------|--------|------|------|------|-------------------|
|                    |               | Min.   | Typ. | Max. |      |                   |
| Current for Driver | $I_{GH}$      | 0.05   | 0.2  | 1.0  | mA   | $V_{GH} = 15.0V$  |
|                    | $I_{GL}$      | 0.2    | 0.5  | 1.0  | mA   | $V_{GL} = -10.0V$ |
|                    | $IDV_{DD}$    | 1      | 4.0  | 10   | mA   | $DV_{DD} = 3.3V$  |
|                    | $I_{AV_{DD}}$ | 5      | 20   | 50   | mA   | $AV_{DD} = 10.4V$ |

## 3.2. Power Sequence

### a. Power on:



| Symbol | SPEC |      |      | Unit |
|--------|------|------|------|------|
|        | Min. | Typ. | Max. |      |
| t1     | 0.5  | 5    | 20   | ms   |
| t2     | 1    | 1    | 1.5  | ms   |
| t3     | 10   | 15   | 20   | ms   |
| t4     | 20   | 22   | 24   | ms   |
| t5     | 1    | 2    | 3    | ms   |
| t6     | 5    | 6    | 7    | ms   |
| t7     | 1.5  | 2    | 4    | ms   |
| t8     | 10   | 12   | 15   | ms   |
| t9     | 10   | 15   | 20   | ms   |

**b. Power off:**

| Symbol | SPEC |      |      | Unit |
|--------|------|------|------|------|
|        | Min. | Typ. | Max. |      |
| t12    | 10   | 15   | 20   | ms   |
| t13    | 5    | 6    | 7    | ms   |
| t14    | 10   | 12   | 15   | ms   |
| t15    | 20   | 22   | 24   | ms   |
| t16    | 1    | 1.5  | 3    | ms   |


### 3.3. Timing Characteristics

#### 3.3.1. AC Electrical Characteristics

| Item            | Symbol           | Values |       |        | Unit | Remark |
|-----------------|------------------|--------|-------|--------|------|--------|
|                 |                  | Min.   | Typ.  | Max.   |      |        |
| HS setup time   | T <sub>hst</sub> | 8      | 10    | 20     | ns   |        |
| HS hold time    | T <sub>hhd</sub> | 8      | 120   | 800    | ns   |        |
| VS setup time   | T <sub>vst</sub> | 8      | 10    | 20     | ns   |        |
| VS hold time    | T <sub>vhd</sub> | 8      | 96000 | 640000 | ns   |        |
| Data setup time | T <sub>dsu</sub> | 8      | 10    | 20     | ns   |        |
| Data hole time  | T <sub>dhd</sub> | 8      | 15    | 20     | ns   |        |

|                                     |                  |    |    |    |    |                                |
|-------------------------------------|------------------|----|----|----|----|--------------------------------|
| DE setup time                       | $T_{\text{esu}}$ | 8  | 15 | 20 | ns |                                |
| DE hole time                        | $T_{\text{ehd}}$ | 8  | 15 | 20 | ns |                                |
| DV <sub>DD</sub> Power On Slew rate | $T_{\text{POR}}$ | 1  | 10 | 20 | ms | From 0 to 90% DV <sub>DD</sub> |
| RESET pulse width                   | $T_{\text{Rst}}$ | 1  | 2  | 5  | ms |                                |
| DCLK cycle time                     | $T_{\text{coh}}$ | 20 | 30 | 40 | ns |                                |
| DCLK pulse duty                     | $T_{\text{cwh}}$ | 40 | 50 | 60 | %  |                                |

### 3.3.2. Input Clock and Data Timing Diagram



### 3.3.3. Timing

| Item                    | Symbol | Values |      |      | Unit | Remark |
|-------------------------|--------|--------|------|------|------|--------|
|                         |        | Min.   | Typ. | Max. |      |        |
| Horizontal Display Area | thd    | /      | 800  | /    | DCLK |        |
| DCLK Frequency          | fclk   | 26.4   | 33.3 | 46.8 | MHz  |        |
| One Horizontal Line     | th     | 862    | 1056 | 1200 | DCLK |        |
| HS pulse width          | thpw   | 1      | 6    | 40   | DCLK | Note1  |
| HS Blanking             | thb    | 46     | 46   | 46   | DCLK | Note1  |

|                |      |    |     |     |      |  |
|----------------|------|----|-----|-----|------|--|
| HS Front Porch | thfp | 16 | 210 | 354 | DCLK |  |
|----------------|------|----|-----|-----|------|--|

| Item                  | Symbol | Values |      |      | Unit | Remark |
|-----------------------|--------|--------|------|------|------|--------|
|                       |        | Min.   | Typ. | Max. |      |        |
| Vertical Display Area | tvd    | /      | 480  | /    | TH   |        |
| VS period time        | tv     | 510    | 525  | 650  | TH   |        |
| VS pulse width        | tpw    | 1      | 3    | 20   | TH   | Note2  |
| VS Blanking           | tvb    | 23     | 23   | 23   | TH   | Note2  |
| VS Front Porch        | tvfp   | 7      | 22   | 147  | TH   |        |

Note1: HS Blanking has included HS pulse width

Note2: VS Blanking has included VS pulse width

Note: Frame rate  $60 \pm 5\text{Hz}$

### 3.3.4. Data Input Format




Figure 3. 1 Horizontal input timing diagram.




Figure 3. 2 Vertical input timing diagram.

## 4. Optical Specifications

Note; Base on INNOLUX LCM

| Item                      | Symbol                 | Condition                       | Values |      |      | Unit   | Remark           |
|---------------------------|------------------------|---------------------------------|--------|------|------|--------|------------------|
|                           |                        |                                 | Min.   | Typ. | Max. |        |                  |
| Viewing angle<br>(CR≥ 10) | $\theta_L$             | $\Phi=180^\circ$ (9 o'clock)    | 60     | 70   | -    | degree | Note 1           |
|                           | $\theta_R$             | $\Phi=0^\circ$ (3 o'clock)      | 60     | 70   | -    |        |                  |
|                           | $\theta_T$             | $\Phi=90^\circ$ (12 o'clock)    | 40     | 50   | -    |        |                  |
|                           | $\theta_B$             | $\Phi=270^\circ$ (6 o'clock)    | 60     | 70   | -    |        |                  |
| Response time             | $T_{ON+}$<br>$T_{OFF}$ | Normal<br>$\theta=\Phi=0^\circ$ | -      | 25   | 50   | msec   | Note 3           |
| Contrast ratio            | CR                     |                                 | 400    | 500  | -    | -      | Note 4<br>Note 7 |
| Color chromaticity        | $W_X$                  |                                 | 0.26   | 0.31 | 0.36 | -      | Note 2<br>Note 5 |
|                           | $W_Y$                  |                                 | 0.28   | 0.33 | 0.38 | -      | Note 6<br>Note 7 |
| Transmittance             | Tr                     | Normal<br>$\theta=\Phi=0^\circ$ | 4.26   | 4.86 | -    | %      | Note 7           |

Test Conditions:

1.  $DV_{DD}=3.3V$ , the ambient temperature is  $25^\circ C$ .
2. The test systems refer to Note 2.

## Note 1: Definition of viewing angle range




Fig. 4-1 Definition of viewing angle

## Note 2: Definition of optical measurement system.

The optical characteristics should be measured in dark room. After 30 minutes operation, the optical properties are measured at the center point of the LCD screen. (Response time is measured by Photo detector TOPCON BM-7, other items are measured by SR3-AR/Field of view:  $1^\circ$ /Height: 500mm.)




Fig. 4-2 Optical measurement system setup

### Note 3: Definition of Response time

The response time is defined as the LCD optical switching time interval between "White" state and "Black" state. Rise time ( $T_{ON}$ ) is the time between photo detector output intensity changed from 90% to 10%. And fall time ( $T_{OFF}$ ) is the time between photo detector output intensity changed from 10% to 90%.




Fig. 4-3 Definition of response time

### Note 4: Definition of contrast ratio

$$\text{Contrast ratio (CR)} = \frac{\text{Luminance measured when LCD on the "White" state}}{\text{Luminance measured when LCD on the "Black" state}}$$

### Note 5: Definition of color chromaticity (CIE1931)

Color coordinates measured at center point of LCD.

Note 6: All input terminals LCD panel must be ground while measuring the center area of the panel.

Note 7: Base on backlight structure of LCM is Diffuser+ BEF +BEF.The color rank of LED is Sa627.





## 5. Reliability Test Items

(Note3)

| Item                                     | Test Conditions                                                                                              | Remark                        |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------|-------------------------------|
| High Temperature Storage                 | Ta = 80℃ 240hrs                                                                                              | Note 1, Note3, Note 4, Note5  |
| Low Temperature Storage                  | Ta = -30℃ 240hrs                                                                                             | Note 1, Note3, Note 4, Note5  |
| High Temperature Operation               | Ts = 70℃ 240hrs                                                                                              | Note 2, Note3, Note 4 , Note5 |
| Low Temperature Operation                | Ta = -20℃ 240hrs                                                                                             | Note 1, Note3, Note 4, Note5  |
| Operate at High Temperature and Humidity | +60℃, 90%RH 240hrs                                                                                           | Note3, Note 4, Note5          |
| Thermal Shock                            | -30℃/30 min ~ +80℃/30 min for a total 100 cycles, Start with cold temperature and end with high temperature. | Note3, Note 4, Note5          |
| Electro Static Discharge                 | ±2KV, Human Body Mode, 100pF/1500 Ω                                                                          |                               |

Note 1: Ta is the ambient temperature of samples.

Note 2: Ts is the temperature of panel's surface.

Note 3: In the standard condition, there shall be no practical problem that may affect the display function. After the reliability test, the product only guarantees operation, but don't guarantee all of the cosmetic specification.

Note 4: Before cosmetic and function test, the product must have enough recovery time, at least 2 hours at room temperature.

Note 5: A certain level of Mura (non-uniformity) of dark / black image will happen several days after high temperature testing (H.T.T.). There is a slowly part recovery over a long time (several months). Such a long exposure time like in H.T.T. will normally not happen in a real application. Therefore the test H.T.T. was introduced to simulate cycles with normal conditions in-between but with the same total exposure time what show a significant reduced Mura.

The root cause is related to tension generated due to different amount of shrinking in the stack of layers in the polarizer sheet. The effect is more significant on larger displays like this size. An investigation into alternative polarizer material showed that there is no better alternative currently available.

## 6. General Precautions

### 6.1. Safety

Liquid crystal is poisonous. Do not put it in your mouth. If liquid crystal touches your skin or clothes, wash it off immediately by using soap and water.

### 6.2. Handling

1. The LCD panel is plate glass. Do not subject the panel to mechanical shock or to excessive force on its surface.
2. The polarizer attached to the display is easily damaged. Please handle it carefully to avoid scratch or other damages.
3. To avoid contamination on the display surface, do not touch the module surface with bare hands.
4. Keep a space so that the LCD panels do not touch other components.
5. Put cover board such as acrylic board on the surface of LCD panel to protect panel from damages.
6. Transparent electrodes may be disconnected if you use the LCD panel under environmental conditions where the condensation of dew occurs.
7. Do not leave module in direct sunlight to avoid malfunction of the ICs.

### 6.3. Static Electricity

1. Be sure to ground module before turning on power or operating module.
2. Do not apply voltage which exceeds the absolute maximum rating value.

### 6.4. Storage

1. Store the module in a dark room where must keep at  $25\pm 10^{\circ}\text{C}$  and 65%RH or less.
2. Do not store the module in surroundings containing organic solvent or corrosive gas.
3. Store the module in an anti-electrostatic container or bag.

### 6.5. Cleaning

1. Do not wipe the polarizer with dry cloth. It might cause scratch.
2. Only use a soft sloth with IPA to wipe the polarizer, other chemicals might permanent damage to the polarizer.





## 8. Package Drawing

### 8.1. Packaging Material Table


| No. | Item               | Model<br>(Material) | Dimensions(mm)   | Unit<br>Weight<br>(kg) | Quantity | Remark |
|-----|--------------------|---------------------|------------------|------------------------|----------|--------|
| 1   | FOG                | NE070NB-04F         | 162.5×96.62×1.43 | 0.046                  | 90       |        |
| 2   | Dust-<br>Proof Bag | PE                  | 700 x 530x0.05   | 0.0579                 | 1        |        |
| 3   | Tray               | PET                 | 472x310x16.4     | 0.196                  | 16       |        |
| 4   | Spacer             | EPE                 | 158.5x92.6x1.5   | 0.001                  | 135      |        |
| 5   | Cushion            | EPE                 | 518x356x90       | 0.14                   | 2        |        |
| 6   | Drier              | SILICA GEL          | 100 x 75         | 0.035                  | 2        |        |
| 7   | Carton             | Corrugated<br>paper | 530 × 367 × 260  | 0.95                   | 1        |        |
| 8   | Total weight       | 8.77± 5% Kg         |                  |                        |          |        |

### 8.2. Packaging Quantity

|                                   |                                          |
|-----------------------------------|------------------------------------------|
| Total LCM quantity of per Carton: | 6 pcs/ tray x15(16-1) tray / Box = 90pcs |
|-----------------------------------|------------------------------------------|



### 8.3. Packaging Drawing



(1) Box Dimensions : 530(L)\*367(W)\*260(H)

(2) 90 panel/Carton